

Appl. No. 10/601,716
Resubmission-Amdt. B dated April 10, 2006
Reply to O.A. of November 1, 2005

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A light emitting device, comprising:
a hollow truncated spherical housing, the housing being substantially transparent and being formed from a crystalline substance; and
a light source positioned at a center point of a sphere defined by a spherical curvature of the housing;
and
a hollow cylindrical housing base having sidewalls of substantially uniform thickness, wherein the housing sits on the housing base.
2. (Original) The light emitting device of claim 1, wherein the hollow truncated spherical housing comprises a hollow hemispherical housing.
3. (Original) The light emitting device of claim 1, where the hollow truncated spherical housing comprises a hollow truncated hemispherical housing.
4. (Original) The light emitting device of claim 1, wherein the housing is of a substantially uniform thickness.
5. (Original) The light emitting device of claim 1, wherein the housing is of a substantially uniform thickness of about 1.2 mm.

Appl. No. 10/601,716
Resubmission-Amdt. B dated April 10, 2006
Reply to O.A. of November 1, 2005

6. (Original) The light emitting device of claim 1, wherein the housing is of a substantially uniform thickness and the thickness of the housing ranges from about 1.2 mm to about 12.7 mm.
7. (Original) The light emitting device of claim 1, wherein the housing terminates in a annular surface having an inner diameter of about 3.2 mm.
8. (Original) The light emitting device of claim 1, wherein the housing terminates in an annular surface having an outer diameter of about 4.4 mm.
9. (Original) The light emitting device of claim 1, wherein the housing terminates in an annular surface having an outer diameter ranging from about 4.4 mm to about 25.4 mm.
10. (Original) The light emitting device of claim 1, wherein the housing terminates in an annular surface wherein the width of the annular surface is about the same as the thickness of the housing.
11. (Canceled)
12. (Previously Presented) The light emitting device of claim 1, wherein the crystalline substance is sapphire.
13. (Canceled)
14. (Original) The light emitting device of claim 1, wherein the light source comprises a solid state light source.

Appl. No. 10/601,716
Resubmission-Amdt. B dated April 10, 2006
Reply to O.A. of November 1, 2005

15. (Original) The light emitting device of claim 1, wherein the light source comprises a Gallium Arsenide light emitting diode.
16. (Original) The light emitting device of claim 1, wherein the light source comprises a light emitting diode.
17. (Original) The light emitting device of claim 1, wherein the light source comprises an infrared light source.
18. (Original) The light emitting device of claim 1, wherein the light source comprise an incandescent light source.
19. (Original) The light emitting device of claim 1, wherein the light source comprises a laser light source.
20. (Original) The light emitting device of claim 1, further including a reflective surface, wherein the light source is disposed between the housing and the reflective surface.
21. (Original) The light emitting device of claim 20, wherein the reflective surface comprises a gold coated surface.
22. *(Canceled)*
23. (Currently Amended) The light emitting device of claim ~~[[22]]~~ 1, wherein the housing base has an upper end and a lower end, wherein the upper end terminates in an inwardly extending flange.

Appl. No. 10/601,716
Resubmission-Amdt. B dated April 10, 2006
Reply to O.A. of November 1, 2005

24. (Currently Amended) A light emitting device, comprising:
a hollow truncated spherical housing having an inner surface and an outer surface, the housing being substantially transparent and being formed from a crystalline substance; [[and]]
a light source for generating a plurality of light rays, the light source being positioned with respect to the housing to minimize an angle of incidence associated with each of the plurality of light rays as they intersect the inner surface of the housing; and
a hollow cylindrical housing base having sidewalls of substantially uniform thickness, wherein the housing sits on the housing base.
25. (Original) The light emitting device of claim 24, wherein the hollow truncated spherical housing comprises a hollow hemispherical housing.
26. (Original) The light emitting device of claim 24, where the hollow truncated spherical housing comprises a hollow truncated hemispherical housing.
27. (Original) The light emitting device of claim 24, wherein the housing is of a substantially uniform thickness.
28. (Original) The light emitting device of claim 24, wherein the housing is of a substantially uniform thickness of about 1.2 mm.
29. (Original) The light emitting device of claim 24, wherein the housing is of a substantially uniform thickness and the thickness of the housing ranges from about 1.2 mm to about 12.7 mm.
30. (Original) The light emitting device of claim 24, wherein the housing terminates in a annular surface having an inner diameter of about 3.2 mm.

Appl. No. 10/601,716
Resubmission-Amdt. B dated April 10, 2006
Reply to O.A. of November 1, 2005

31. (Original) The light emitting device of claim 24, wherein the housing terminates in an annular surface having an outer diameter of about 4.4 mm.
32. (Original) The light emitting device of claim 24, wherein the housing terminates in an annular surface having an outer diameter ranging from about 4.4 mm to about 25.4 mm.
33. (Original) The light emitting device of claim 24, wherein the housing terminates in an annular surface wherein the width of the annular surface is about the same as the thickness of the housing.
34. (Canceled)
35. (Previously Presented) The light emitting device of claim 24, wherein the crystalline substance is sapphire.
36. (Cancelled)
37. (Original) The light emitting device of claim 24, wherein the light source comprises a solid state light source.
38. (Original) The light emitting device of claim 24, wherein the light source comprises a Gallium Arsenide light emitting diode.
39. (Original) The light emitting device of claim 24, wherein the light source comprises a light emitting diode.

Appl. No. 10/601,716
Resubmission-Amdt. B dated April 10, 2006
Reply to O.A. of November 1, 2005

40. (Original) The light emitting device of claim 24, wherein the light source comprises an infrared light source.

41. (Original) The light emitting device of claim 24, wherein the light source comprise an incandescent light source.

42. (Original) The light emitting device of claim 24, wherein the light source comprises a laser light source.

43. (Original) The light emitting device of claim 24, further including a reflective surface, wherein the light source is disposed between the housing and the reflective surface.

44. (Original) The light emitting device of claim 43, wherein the reflective surface comprises a gold coated surface.

45. *(Cancelled)*

46. (Currently Amended) The light emitting device of claim ~~[[45]]~~ 24, wherein the housing base ~~has comprises a hollow cylindrical body having~~ an upper end and a lower end, wherein the upper end terminates in an inwardly extending flange.

47. (Previously Presented) The light emitting device of claim 1, wherein the crystalline substance is diamond.

Appl. No. 10/601,716
Resubmission-Amdt. B dated April 10, 2006
Reply to O.A. of November 1, 2005

48. (Previously Presented) The light emitting device of claim 1, wherein the crystalline substance is quartz.

49. (Previously Presented) The light emitting device of claim 20, wherein the light source and the reflective surface are mounted on a conductive pin.

50. (Previously Presented) The light emitting device of claim 24, wherein the crystalline substance is diamond.

51. (Previously Presented) The light emitting device of claim 1, wherein the crystalline substance is quartz.

52. (Previously Presented) The light emitting device of claim 43, wherein the light source and the reflective surface are mounted on a conductive pin.

53. (Previously Presented) A light emitting device, comprising:
a hollow truncated spherical housing, the housing being substantially transparent;
a light source positioned at a center point of a sphere defined by a spherical curvature of the housing;
and
a hollow cylindrical housing base, wherein the housing sits on the housing base.

54. (Currently Amended) The light emitting device of claim ~~[[54]]~~ 53, wherein the housing base has an upper end and a lower end, wherein the upper end terminates in an inwardly extending flange.

55. (Currently Amended) A light emitting device, comprising:
a hollow truncated spherical housing having an inner surface and an outer surface, the housing being

Appl. No. 10/601,716

Resubmission-Amdt. B dated April 10, 2006

Reply to O.A. of November 1, 2005

substantially transparent and being formed from a crystalline substance;
a ~~light source~~ light emitting diode for generating a plurality of light rays, the light source being positioned with respect to the housing to minimize an angle of incidence associated with each of the plurality of light rays as they intersect the inner surface of the housing; and
a hollow cylindrical housing base, wherein the housing sits on the housing base.

56. (Previously Presented) The light emitting device of claim ~~[[56]]~~ 55, wherein the housing base has an upper end and a lower end, wherein the upper end terminates in an inwardly extending flange.

57. (New) The light emitting device of claim 56, wherein the light emitting diode comprises an infrared light emitting diode.